



Safety Data Sheet

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System
Date of Revision: 05/02/2022 Revision: 0

Section 1 - Chemical Product and Company Identification

- 1.1 Product Brand: VP Racing Hobby Fuels
- 1.1.1 Product Name: 30% Ryan Lutz, 9%Oil
- 1.2 Blend
- 1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744
- 1.4 Recommended Use: R/C Model Engine Fuel
- 1.5 **RESTRICTIONS on USE THIS FUEL IS FOR R/C MODEL ENGINE USE ONLY!**
- 1.6 Emergency Response Number: CHEMTREC 800-424-9300
Local Emergency Telephone Number: +1-703-527-3887
- 1.7 See Section 16.3 for CHEMTREC in Country Emergency Number

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes

Flammable liquid
 Specific Target Organ Toxicity single exposure
 Acute Toxicity (Oral)
 Acute Toxicity (Inhalation)
 Acute Toxicity (Dermal)

Hazard Categories

Category 2
 Category 1
 Category 3
 Category 3
 Category 3

2.2 Signal Word: **Danger**

2.3 Pictograms:



Flame Health Hazard Toxic

**VP Racing Hobby Fuels
30% Ryan Lutz, 9%Oil**

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

2.4 Hazard Statements

PHYSICAL HAZARDS:	H225: Highly flammable liquid and vapor.
HEALTH HAZARDS:	H301: Toxic if swallowed H311: Toxic in contact with skin. H332: Toxic if inhaled. H370: May cause damage to organs.
ENVIRONMENTAL HAZARDS:	None
PRECAUTIONARY STATEMENTS:	P102: Keep out of reach of children. P210: Keep away from sparks and open flames- No smoking. P240: Ground or bond container and receiving equipment. P241: Use explosion-proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260: Do not breathe vapors. P264: Wash hands thoroughly after handling. P270: Do not eat, drink, or smoke when using this product P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves, clothing, and eye protection.
RESPONSE STATEMENTS:	P301 +310+ P331: IF SWALLOWED: <u>USA</u> Immediately call the National POISON CENTER at 800-222-1222, <u>OUTSIDE USA</u> Immediately call a poison center or doctor. DO NOT induce vomiting. P302+P352: IF on SKIN, wash with plenty of water. P304+340: IF INHALED: Remove to fresh air and keep comfortable for breathing. P308+P311: If exposed or concerned: Call the poison center or doctor. P330: Rinse mouth. P361: Take off immediately all contaminated clothing and wash before reuse. P370+P378: In case of a fire, use foam, carbon dioxide, and dry chemical to extinguish the fire.
STORAGE STATEMENTS:	P403+P235: Store in a well-ventilated place. Keep cool. P405: Store locked up.

**VP Racing Hobby Fuels
30% Ryan Lutz, 9%Oil**

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

DISPOSAL STATEMENTS:

P501: Dispose of content and container following local, regional, national, or international regulations.

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Repeated exposure may cause skin dryness or cracking.

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Classification
67-56-1	200-659-6	Methanol	58-64	Flam. Liq. H225, Acute Tox. H301, Acute Tox. 3, H311, Acute Tox. 3, H331, STOT SE1 H370
75-52-5	200-876-6	Nitromethane	28-35	Flam Liq. 3 H226, Acute Tox 4 H302,
25322-69-4	500-039-8	Propylene oxide homopolymer	4-8	Not classified
8001-79-4	232-293-8	Castor oil	1-5	Not classified

3.2 Trade Secret Provision and Chemical Concentration Disclosure: Following OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a range applicable to the hazards identified in this Safety Data Sheet.

Section 4 - First Aid Measures

General information: Ensure that medical personnel knows the material(s) involved and take precautions to protect themselves.

Following Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Following Skin contact: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

Following eye contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Following ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

4.2.2: Prolonged and repeated liquid contact with the skin can cause defatting and drying and lead to irritation and dermatitis.

VP Racing Hobby Fuels 30% Ryan Lutz, 9%Oil

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

4.2.3: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities can produce chemical pneumonia, pulmonary edema, and even death.

4.2.4: Prolonged breathing of high vapor concentrations can produce headaches, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage, and death resulting from respiratory failure.

4.3 Indication of any immediate medical attention and special treatment needed: The severity of outcome following exposure may be related to the time between the exposure and treatment rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

Note to Physicians: If you determine that a medical emergency exists. The specific chemical identity is necessary for emergency or first-aid treatment and will be immediately disclosed the specific chemical identity. Call CHEMTREC 800-424-9300 or +1-703-527-3887. We will require a written statement of need and confidentiality agreement as soon as circumstances permit. In non-emergency situations, we will, upon written request, disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

General fire hazards: Highly flammable liquid and vapor.

5.1 Extinguishing media:

Suitable extinguishing media: Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media: Do not use a water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture: Vapors may form explosive mixtures with air. Vapors may travel a considerable distance to a source of ignition and flashback. During a fire, gases hazardous to health may be formed.

5.3 Advice for firefighters: Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

Additional information: Do not release runoff from fire to sewers or waterways.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment, and emergency procedures:

6.1.1 For non-emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spills and leaks. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the immediate area. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

6.1.2 For emergency responders: Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use personal protection recommended in Section 8 of the SDS.

VP Racing Hobby Fuels 30% Ryan Lutz, 9%Oil

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

6.2 Environmental precautions: Avoid direct contact with the material. Stop leak if without risk. Move containers from the spill area. Prevent entry into sewers or waterways.

6.3 Methods and material for containment and cleaning up:

6.3.1 For containment: Eliminate all ignition sources (no smoking, flares, sparks, or flames in the immediate area). Keep combustibles such as wood, paper, and oil) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewers, basements, or confined areas.

6.3.2 For clean up:

6.3.2.1 Small spill; Absorb with earth, sand, or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

6.3.2.2 Large spill: Stop the material flow if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand, or earth to soak up the product and place it into a container for later disposal. Following product recovery, flush the area with water.

6.3.3 Other information: Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

6.4 Reference to other sections: See section 8 of the SDS for personal protection. For waste disposal, see section 13 of the SDS.

Section 7 - Handling and Storage

7.1 Precautions for safe handling: Avoid breathing vapors. Avoid contact with eyes, skin, and clothing. Avoid contact with eyes. Observe good industrial hygiene practices. Provide adequate ventilation. Take precautionary measures against static discharge. Eliminate all ignition sources. No smoking, flames, sparks, or flames in the immediate area., Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Launder contaminated clothing before reuse. Avoid release to the environment. Observe good industrial hygiene practices.

7.1.1 Bonding and grounding plastic containers: The requirements for bonding and grounding of containers during the transfer of Class I flammable liquids are contained in 29 CFR 1910, paragraph (e)(6)(ii). This paragraph does not specifically address plastic containers. OSHA has issued "OSHA Instruction STD 1-5.14-A" on October 24, 1980, to address it,

When bonding and grounding two non-conductive containers, a static electrical charge can be generated when two dissimilar materials (Metal and Plastic) pass quickly by one another OSHA recognizes that many factors affect the size and strength of the static charge or potential that may develop such as speed of transfer, humidity, container size, and others. OSHA is concerned that any static charge between two containers is equalized, if not eliminated, so no potential for a static discharge exists. Therefore, OSHA will permit the transfer of Class I liquids between plastic or other non-conductive containers under the following conditions:

1. A non-conductive container must be equipped with an approved metallic suction pump and draw tube for taking liquid from the top of a plastic container. The pump must be electrically grounded.
2. The non-conductive container must be equipped with a metallic, self-closing faucet that can be grounded electrically.

VP Racing Hobby Fuels 30% Ryan Lutz, 9%Oil

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Additionally, OSHA stated: The transfer of Class I flammable liquids between small containers may not require special bonding and grounding techniques. NFPA 77-1993 states that containers of glass or other non-conductive materials of five gallons or less capacity are usually filled without special precautions." However, for larger containers, NFPA 77-1993 suggests that special techniques should be used to handle flammable liquids in plastic containers with 5 to 60 gallons. OSHA would consider compliance with the suggestions of NFPA 77-1993 regarding the bonding and grounding of plastic containers holding Class I flammable liquids as compliance with meeting the intent of OSHA's standards in 29 CFR 1910.106, paragraphs (e)(6)(ii) and (d)(2)(iii)." (From OSHA Response letter about grounding on March 29, 1999).

7.2 Conditions for safe storage, including any incompatibilities: Store locked up in a cool, dry, well-ventilated place out of direct sunlight. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a tightly-closed container. Store in a. Store away from incompatible materials (see section 10).

7.3 Specific end use(s): Model racing fuel only.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Nitromethane	20ppm TWA	100 ppmTWA
Methanol	200ppm TWA	200ppmTWA
Castor oil	Not Established	Not Established
Propylene oxide homopolymer	Not Established	Not Established

8.2 ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.

OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour workweek which shall not be exceeded.

8.3 Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.4 Contaminated Equipment: Separate contaminated work clothes from street clothes and launder them before reuse. Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows that air-purifying respirators are appropriate, use a full-face respirator with a multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied-air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Butyl-rubber

Splash contact: Nitrile rubber

8.5.3 Eye protection

VP Racing Hobby Fuels 30% Ryan Lutz, 9%Oil

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid

Appearance: Various

Odor: Aromatic Alcohol odor

Vapor Pressure: Not Available

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1): Not Available

Relative Density: Not Available

Odor Threshold: Not Available

Flammability (solid, gas): Not Applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not Available

Water Solubility: Slightly soluble

Flash Point: 52°F (11°C) c.c. (Estimated)

Boiling Point: 148.5°F (64.7°C) (Estimated)

Lower Explosive Limits (vol % in air): Not Available

Upper Explosive Limits (vol % in air): Not Available

Melting Point: Not Available

Viscosity: Not Available

Autoignition Temperature: Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks, open flames, and other ignition sources.

Section 11- Toxicological Information

11.1 Acute Toxicity Estimate for this blend (ATE)

ATE (Oral): 301.2 mg/kg

ATE (Dermal): 994 mg/kg

ATE (Inhalation vapor/mist): 9.8 mg/l

11.1.1 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components be Acute Toxic Oral Toxicity.

VP Racing Hobby Fuels 30% Ryan Lutz, 9%Oil

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

11.11.2 OECD Guideline Test results found in the European Chemical Agency Database show that this product's components are Acute Harmful Inhalation Toxicity.

11.11.3 OECD Guideline Test results found in the European Chemical Agency Database show this product's components to Acute Harmful Dermal Toxicity.

11.2 Route of Entry: Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

11.3 Aspiration Hazard: European Chemical Agency Database shows that no product components may be fatal if swallowed and enters the airways.

11.4 Mutagenicity: OECD Guideline Tests results found in the European Chemical Agency Database show no product components cause genetic defects.

11.5 Skin Corrosion/Irritation: OECD Guideline Tests results found in the European Chemical Agency Database shows that no product components cause skin irritation. However, it can still irritate your skin.

11.6 Serious Eye Damage/Irritation: OECD Guideline Test results found in the European Chemical Agency Database show that no product components cause serious eye irritation. However, it can still irritate your eyes.

11.7 Reproductive toxicity: OECD Guideline Tests results found in the European Chemical Agency Database show no components of this product to cause damage to fertility or the unborn child. However, California's PROP 65 regulations show that components of this blend can cause damage to fertility or the unborn child.

11.8 Skin Sensitisation: OECD Guideline Test results in the European Chemical Agency Database show no product components cause skin sensitivity.

11.9 Respiratory Sensitisation: OECD Guideline Test results found in the European Chemical Agency Database show no product components cause respiratory sensitivity.

11.10 Specific Target Organ Toxicity (Single Exposure): None. However, components may cause damage to the following organs: Blood, thyroid, and respiratory system.

11.11 Specific Target Organ Toxicity (Repeated Exposure): European Chemical Agency Database shows that this product's components may cause damage to the following organs: Blood, thyroid, and respiratory system.

11.12 Signs and Symptoms: Effects of overexposure can include Methyl alcohol may be fatal or cause blindness if swallowed. Effects due to ingestion may include Headache, Dizziness, Drowsiness, metabolic acidosis, Coma, and Seizures. Symptoms may be delayed.

11.13 Carcinogenicity: OECD Guideline Test results in the European Chemical Agency Database show that no product components can cause cancer. However, The American Conference of Governmental Industrial Hygienists shows this blend's components as a human carcinogen.

**VP Racing Hobby Fuels
30% Ryan Lutz, 9%Oil**

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Nitromethane	LC50 460 mg/l	Fish	48 hours
Nitromethane	EC50 450 mg/l	Daphnia	24 hours
Nitromethane	IC50 36 mg/l	Aquatic	72 hours
Methanol	LC50 29.4 g/L	Fish	96 hours
Methanol	LC50 22,200 mg/L	Daphnia magna	48 hours
Castor oil	None Listed	None Listed	None Listed
Propylene oxide homopolymer	LC50 > 100 mg/l	Fish	96 hours

Toxicity: OECD Guideline Test results found in the European Chemical Agency Database show no components of this product to cause long-term toxicity to aquatic life.

12.2 Mobility: Floats on water

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! The container should be completely emptied before being discarded. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 DOT Transport Information



ID No.: UN 1993

Shipping Name: Flammable liquids, n.o.s. (Nitromethane, Methanol)

Hazard Class: 3

Packing Group: II

Label: Flammable


Placard: Flammable

14.2 IMDG Transport Information

**VP Racing Hobby Fuels
30% Ryan Lutz, 9%Oil**

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

14.2 IMDG Transport Information



ID No.: UN 1992

Shipping Name: FLAMMABLE LIQUIDS, TOXIC, NOS (Nitromethane, methanol)

Hazard Class: 3, (6.1)

Packing Group: II

Flash Point: 11°C - closed cup

EmS Number: F-E, S-E

Label: Flammable, Toxic

Placard: Flammable, Toxic

14.3 UN Dangerous Goods Transport Information



ID No.: UN 1992


Shipping Name: Flammable liquids, toxic, n.o.s. (Nitromethane, Methanol)

Hazard Class: 3, (6.1)

Packing Group: II

Label: Flammable, Toxic

Placard: Flammable, Toxic



Use marking when shipping as a limited quantity by ground.

14.4 DOT Transport Limited Quantity


Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

**VP Racing Hobby Fuels
30% Ryan Lutz, 9%Oil**

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System



Use marking when shipping as a limited quantity by vessel.

14.5 IMDG Transport Limited Quantity

Inner packaging not over

1.0L (0.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

ID No.: UN 1992

Shipping Name: FLAMMABLE LIQUIDS, TOXIC, NOS (Nitromethane methanol) LTD QTY

Hazard Class: 3, (6.1)

Packing Group: II

Flash Point: 11°C - closed cup

EmS Number: F-E, S-E

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

Toxic Release Inventory (TRI): This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
67-56-1	Methanol	64%
75-52-5	Nitromethane	35%

This information must be included in all SDSs copied and distributed for this material.

CERCLA Hazardous Substances and corresponding RQs: Methanol 5000 pounds.

SARA Community Right-to-Know Program: All components of this blend.

Clean Water Act: None

Clean Air Act: None

OSHA: All ingredients are listed in 29 CFR1910.1200.

OSHA Process Safety Management (PSM) List: Nitromethane 2500 lbs.

California prop. 65



WARNING This product can expose you to chemicals, including Nitromethane CAS # 75-52-5 and Methanol CAS # 67-56-1, known to California to cause cancer, birth defects, or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

VP Racing Hobby Fuels 30% Ryan Lutz, 9%Oil

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

Pennsylvania: All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

15.2 International Regulations:

Australian Inventory of Chemical Substances: All components of this product are on the Inventory or are exempt from Inventory requirements.

National Existing Chemical Inventory in Taiwan: All components of this product) are on Inventory or are exempt from Inventory requirements.

Philippine Inventory of Chemicals and Substances All components of this product are on the Inventory or exempt from Inventory requirements.

China Existing Chemical Inventory: All components of this product are in the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and assume the risk of its use.

16.2 References: CHEMpendium Database of Canadian Centre for Occupational Health and Safety (CCOHS), European Chemical Agency Database, NORA CAMEO Chemicals Database, and MSDS and SDS of chemicals in this mixture.

16.3 CHEMTREC in-country emergency dial numbers:

County	Greeting Language	City	Local number	Toll-Free number
Argentina	Latin American Spanish	Buenos Aires	54-1159839431	
Brazil	Portuguese	Rio De Janeiro	55-2139581449	
Brazil	Portuguese	Sao Paulo	55-1143491359	
Brazil - Toll-Free	Portuguese		0800 892 0479	0800 892 0479
Cayman Islands	English	Local (National)	345-749-8392	
Chile	Latin American Spanish	Santiago	56 2 2581 4934	
Colombia	Latin American Spanish		01800-710-2151	01800-710-2151

**VP Racing Hobby Fuels
30% Ryan Lutz, 9%Oil**

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Costa Rica	Latin American Spanish		506-40003869	
Dominican Republic	Latin American Spanish	Santo Domingo	1 (829) 956-7588	
El Salvador	Latin American Spanish	San Salvador	503 2136 7633	
Grenada	English	St George	1 (473) 230-0165	
Guinea	French		224 660 71 03 00	
Mexico	Latin American Spanish		01-800-681-9531	01-800-681-9531
Panama	Latin American Spanish		507-8322475	
Peru	Latin American Spanish	Lima	51-17071295	
Trinidad and Tobago	English	National Number	1-868-224-5716	
India	Hindi, Bengali, English		000-800-100-7141	000-800-100-7141
Indonesia	Indonesian		001-803-017-9114	001-803-017-9114
Israel	Hebrew	Tel Aviv	972-37630639	
Japan	Japanese	Tokyo	81-345209637	
Malaysia	Malay	Kuala Lumpur	60-392125794	1-800-815-308
Philippines	Tagalog	Manila	+63 2 8395 3308 and 1-800-1-116-1020	1-800-1-116-1020
Russia	Russian		8-800-100-6346	8-800-100-6346
Saudi Arabia	Arabic and English		966-8111095861	
Singapore	English and Mandarin		65-31581349	800-101-2201
South Korea	Korean			003-0813-2549 and 080-822-1374
Taiwan	Mandarin	Taipei	886-2-7741-4207	00801-14-8954
Thailand	Thai		001-800-13-203-9987	001-800-13-203-9987

County	Greeting Language	City	Local number	Toll-Free number
Australia	English	Sydney	61-290372994	
New Zealand	English	Auckland	64-98010034	

**VP Racing Hobby Fuels
30% Ryan Lutz, 9%Oil**

Conforms to OSHA 29 CFR 1910.1200 and aligns to the United Nations Globally Harmonized System

Country	Greeting Language	City	Local number	Toll-Free number
South Africa	English	None	0-800—983-611	0-800—983-611

16.4 SDS Preparation Date 04/24/2022

SDS Previous Issue Date: None

Prepared by SJC Compliance Education, Inc.
1319 Varese Dr.
Pearland, TX 77581
steve@sjcedu.org

END OF SAFETY DATA SHEET